

BALKAN MOTOR SANAYİ VE TİCARET A.Ş. Since 1953

- Protection class: 0
- Insulation class: F
- Motor shaft: Ck45
- RFI suppressor: 18µH 3A choke coil
- Cables: H05V-K 0.50mm² VDE approved
- Bearings: Sinter Bronze.

Universal Motor 230V(BM64E 964.94.013)





MOTOR TYPE	MOTOR CODE	TEST VOLT. (V)	TEST FREQ. (Hz)	SPEED STEP	MOTOR PERFORMANCE VALUES													
					At No Load		At Stall		At Maximum Efficiency					At Maximum Power				
					Speed (RPM)	Cur. (Amp)	Torque (Ncm)	Cur. (Amp)	Torque (Ncm)	Speed (RPM)	Cur. (Amp)	Eff. (%)	Pout (W)	Torque (Ncm)	Speed (RPM)	Cur. (Amp)	Eff. (%)	Pout (W)
BM64E	964.94.013	230	50	1	19944	0.563	52.6	4.012	11.88	12158	1.449	49.84	151.3	27.02	7190	2.635	39.19	203.48
				2	21311	0.625	62.83	5.203	11.94	13548	1.537	50.67	169.39	34.43	7183	3.414	37.52	259.01





Remarks:
- Documents here includes only reference values.BALKAN MOTOR A.Ş. has the right to revise them without any prior information.
- BALKAN MOTOR A.Ş. could modify all its products according to customer requirements.

BALKAN MOTOR SANAYİ VE TİCARET A.Ş.
Yenibosna Sanayi Caddesi No:21 34530 Bahçelievler/İstanbul/TURKEY
Tel:+90 (212)551 01 00 (7 Lines) Fax: +90 (212) 551 31 67 www.balkanmotor.com e-mail: balkan@balkanmotor.com

TÜV International Certification TÜV THÜRINGEN TIC
Quality management system ISO 9001
• Customer focus
• Customer satisfaction
• Continuous improvement
• System/process effectiveness
ID 15 100 53007
www.tuev-thueringen.de